

APÉNDICE C

LISTA DE CODALES DEL DISTRIBUIDOR ISCHEBECK®¹

MODELO DE CODAL	LONGITUD DE CODAL CON RESPECTO AL ANCHO DE LA EXCAVACIÓN				SOPORTE DE CARGA O FUERZA DEL CODAL			
	MINIMA		MAXIMA		MINIMA		MAXIMA	
	SMD (M)	SI (FT)	SMD (M)	SI (FT)	SMD (Kn)	SI (kLb)	SMD (Kn)	SI (kLb)
Gi-SV-210	1.40	4.59	2.10	6.89	340.00	76.44	345.00	77.56
Gi-SV-260	1.90	6.23	2.60	8.53	340.00	76.44	345.00	77.56
Gi-SV-310	2.40	7.87	3.10	10.17	340.00	76.44	345.00	77.56
Gi-SV-380	3.10	10.17	3.80	12.47	253.00	56.88	253.00	56.88
Gi-SV-450	3.80	12.47	4.50	14.76	253.00	56.88	253.00	56.88
Gi-S-170	1.00	3.28	1.70	5.58	177.00	39.79	210.00	47.21
Gi-S-210	1.40	4.59	2.10	6.89	156.00	35.07	184.00	41.36
Gi-S-260	1.90	6.23	2.60	8.53	140.00	31.47	176.00	39.57
Gi-S-310	2.40	7.87	3.10	10.17	138.00	31.02	157.00	35.30
Ti-60/150	0.90	2.95	1.50	4.92	99.00	22.26	100.00	22.48
Ti-60/200	1.40	4.59	2.00	6.56	93.00	20.91	100.00	22.48
Ti-60/250	1.90	6.23	2.50	8.20	84.00	18.88	95.00	21.36
Ti-60/300	2.40	7.87	3.00	9.84	72.00	16.19	85.00	19.11
Gi-L-120	0.70	2.30	1.17	3.84	48.00	10.79	63.00	14.16
Gi-L-150	0.90	2.95	1.50	4.92	45.00	10.12	61.00	13.71
Gi-L-210	1.20	3.94	2.10	6.89	39.00	8.77	60.00	13.49
terra No. 1	0.50	1.64	0.80	2.62	30.00	6.74	38.00	8.54
terra No. 1a	0.60	1.97	0.90	2.95	29.00	6.52	36.00	8.09
terra No. 2	0.80	2.62	1.10	3.61	29.00	6.52	34.00	7.64
terra No. 3	1.10	3.61	1.40	4.59	23.00	5.17	29.00	6.52
terra No. 4	1.47	4.82	1.70	5.58	22.00	4.95	26.00	5.85

Tabla C.1 Codales Ischebeck®

¹ www.ischebeck.es pdf.- tablestacado.pdf pág. 9