

Apéndice D

Configuración de Kannel

A continuación se muestra el listado de las configuraciones usadas para las pruebas de este proyecto, para más detalles sobre la configuración de Kannel, visite: <http://www.kannel.org/userguide.shtml>.

```
1 group = core
2 admin-port = 6669
3 admin-password = f00bar
4 status-password = f00bar
5 admin-deny-ip = " *.*.*.* "
6 admin-allow-ip = "127.0.0.1"
7 smsbox-port = 6667
8 # wapbox-port = 6668
9 box-deny-ip = " *.*.*.* "
10 box-allow-ip = "127.0.0.1"
11 wdp-interface-name = "*"
12 log-level = 4
13 log-file = "/home/tesis/Kannel/log/bearer.log"
14 access-log = "/home/tesis/Kannel/log/kannel.access"
15
16 group = smsbox
17 bearerbox-host = localhost
18 sendsms-port = 64235
19 global-sender = 4378
20 reply-couldnotfetch = "Contacta_a_soporte_code_1"
21 reply-couldnotrepresent = "Contacta_a_soporte_code_2"
```

```
22 reply-requestfailed = "Contacta_a_soporte_code_3"
23 reply-emptymessage = "Contacta_a_soporte_code_4"
24 http-request-retry = 120
25 http-queue-delay = 1
26 log-level= 1
27 log-file = "/home/tesis/Kannel/log/smsbox.log"
28
29
30 group = smsc
31 smsc = smpp
32 smsc-id = test_00
33 host = localhost
34 port = 10001
35 transceiver-mode = true
36 smsc-username = pavel
37 smsc-password = pavel
38 system-type = VMA
39 interface-version = 0x34
40 enquire-link-interval = 60
41 max-pending-submits = 10
42 reconnect-delay = 30
43 source-addr-ton = 0
44 source-addr-npi = 1
45 source-addr-autodetect = true
46 dest-addr-ton = 2
47 dest-addr-npi = 1
48 alt-charset = "UTF-8"
49 log-level = 1
50 log-file = "/home/tesis/Kannel/log/test_00.log"
51
52 group = sms-service
53 keyword = default
54 text = "hola_mundo"
55 max-messages = 1
56
57
58 group = sendsms-user
59 username = foo
60 password = bar
61 concatenation = 0
62 max-messages = 4
```
